

QJIA **PRO**
MONOFACIAL

BSM585PMB6-60SC

570~590W

SHINGLED PERC

BLUESUN SOLAR CO.,LTD

Bluesun, founded in 2004, as a superior photovoltaic manufacturer, is devoted to the R&D and the production of crystalline silicon solar cells and modules for 17 years. The company has its sales areas spread all over more than 100 countries and regions in the world, and the cumulative historical shipments exceeded 12 GW.

PERFORMANCE WARRANTY

- 15** Enhanced Product Warranty on Materials and Workmanship.
- 30** Linear Power Performance Warranty*
- 55** Annual Degradation Over 30 years no more than 0.55%



*According to the applicable Bluesun Solar Limited Warranty Statement.

MANAGEMENT SYSTEM CERTIFICATES

- ISO 9001:2015 / Quality management system
- ISO 14001:2015 / Standards for environmental
- ISO 45001: 2018 / International standards for occupational health & safety

PRODUCT CERTIFICATES

IEC 61215 / IEC 61730 / CE



THE IDEAL SOLUTION FOR:



Ground-mounted solar power plants



Shingled Technology

Innovative structure, low -temperature adhesive bonding, high-density layout



Beautiful Appearance

Uniform layout, better aesthetic



Superior safety and Reliability

No hidden welding crack, low operating temperature, high pressure resistance



Low System Cost

High module efficiency, reducing system cost



Low Shading Loss


Full parallel arrangement brings high effective power generation hours

SPECIFICATIONS


Module Type	BSM570PMB6-60SC		BSM575PMB6-60SC		BSM580PMB6-60SC		BSM585PMB6-60SC		BSM590PMB6-60SC	
	STC	NMOT								
Maximum Power (P _{max} /W)	570	426	575	434	580	438	585	442	590	446
Operating Voltage (V _{mp} /V)	39.5	37.50	39.60	37.70	39.70	37.80	39.80	37.90	39.90	38.00
Operating Current (I _{mp} /A)	14.44	11.36	14.53	11.52	14.62	11.59	14.71	11.67	14.80	11.74
Open-Circuit Voltage (V _{oc} /V)	47.50	45.20	47.60	45.40	47.70	45.50	47.80	45.67	47.90	45.70
Short-Circuit Current (I _{sc} /A)	15.36	12.30	15.46	12.46	15.56	12.55	15.65	12.63	15.75	12.71
Module Efficiency η _m (%)	21.60		22.00		22.20		22.40		22.60	

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5 NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Air Mass AM1.5, Wind Speed 1m/s

I-V CURVE



ENGINEERING DRAWINGS



MECHANICAL SPECIFICATION

Cell Type	Mono-crystalline solar cell
Cell Dimensions	210*210mm
Cell Orientation	345 (69*5)
Weight	28.3kg
Module Dimensions	2384*1096*35mm
Cable Length	Portrait 300mm/Landscape 1200mm/Customized
Cable Cross Section Size	TUV: 4mm ² (0.006inches ²)/UL: 12AWG
Front Glass	3.2mm (0.13inches) AR Coating Tempered Glass
No. of Bypass Diodes	3
Packing Configuration	31pcs/carton, 620pcs/40hq
Frame	Anodized Aluminium Alloy
Junction Box	IP68

OPERATING CONDITIONS

Maximum System Voltage	1500V/DC(IEC)
Operating Temperature	-40°C~ +85°C
Maximum Series Fuse	25A
Static Loading	Snow Loading: 5400Pa/ Wind Loading: 2400Pa
Conductivity at Ground	≤0.1Ω
Safety Class	II
Resistance	≥100MΩ
Connector	T01/LJQ-3-CSY/MC4/MC4-EVO2

TEMPERATURE COEFFICIENT

Temperature Coefficient P _{max}	-0.34%/°C
Temperature Coefficient V _{oc}	-0.27%/°C
Temperature Coefficient I _{sc}	+0.04%/°C
NMOT	42.3±2°C

*Data contained in these specifications is subject to change without notice. Bluesun Solar reserves the right to final interpretation of content.